This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS


IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.




27.12				_ .	100
1			^	1122	
₩ ¥	140	CV	Marian.	HET	
100	100		w	III O L	_
		ok S			4

1-1/1 Next page From 1 - 1 Count
Display format Select the type of output
Display checked documents
CheckAll UncheckAll WincheckAll
Application no/date: 1985-130746[1985/ 8/27] Date of request for examination: [] Accelerated examination ()
Public disclosure no/date: 1987-39007 Translate [1987/3/9] Examined publication no/date (old law): [] Registration no/date: [] Examined publication date (present law): [] PCT application no: PCT publication no/date: [] Applicant: NISSAN MOTOR CO LTD
Inventor: MATSUNAGA YUSUKE IPC: F16B 5/06 B60R 13/04 F16B 21/06 F16B 21/08 FI: F16B 5/06 F16B 21/06 A F16B 21/08 F16B 5/06 B B60R 13/04
F-Term: 3J001AA07, BB02, DB03, DC03, DE05, EA01, EA02, 3D023AA01, AA03, AB01, AC01, AD11, AD26, 3J037AA02, BB07, DA01, DA11, DA13, DB01, DC02, DC05, 3J001FA18, GA06, GB01, GC07, HA02, HA07, JD26, KA14, KA25, KA26, KB01 Expanded classicication: 221, 262 Fixed keyword: Citation: [, , , ,] (, , ,) Title of invention: The mount which consists of clip and grommet Abstract: [ABSTRACT]
Because length was extended in a longitudinal direction of the second n that locking pore comprised clip of at least one grommet appropriately, even if the member of framework expands and contracts by a telescopic n or a dimension error of resin accessories longitudinally, and clip dist expands and contracts to some extent, clip can be put in grommet. Additional word: Side guard track bolt, automotive body panel



.

Priority country/date/number: () [] ()
Domestic priority: [] ()
Original application number: ()
Original registration number: ()
Retroactive date:[]
No. of claims (1)
Classification of examiners decision/date: () []
Final examinational transaction/date: (
withdrawal by no request for examination) [1989/10/31]
Examination intermediate record:
(A63 1985/ 8/27, PATENT APPLICATIONUTILITY MODEL REGISTRATION APPLICATION,
7100:)
(A7D2 1989/ 5/20, NOTIFICATION OF LUMP CHANGE IN DOMICILE (REPRESENTATIVE),
:)
(A300 1989/10/19, MAKING OF FILE WRAPPER EXTRACTION LIST OF UNREQUEST FOR EXA
MINATION, :)
*** Trial no/date [] Kind of trial [
Demandant: -
Defendand: -
Opponent: -
Classification of trial decision of opposition/date: () []
Final disposition of trial or appeal/date: () [
Trial and opposition intermediate record:
illar and opposition intermediate record:
Registration intermediate record:
Registration intermediate record:
Amount of annuity payment:
Extinction of right/Lapse date of right: ()[]
Proprietor: -
Status of register: ()
© Other Diewing :
Check All Uncheck All
Display Greeked doomments
English American Condition (1)
Display format Select the type of output
Display format
1-1/1 Rexipage From 1 - 1 Count
· Backtolist
· Economics)



⑩日本国特許庁(JP)

①実用新案出願公開

母 公開実用新案公報(U)

昭62-39007

6)Îı	ni	Cl	.*

識別記号

庁内整理番号

❸公開 昭和62年(1987)3月9日

F 16 B 5/06 B 60 R 13/04 F 16 B 21/06 B-6673-3J 7401-3D A-8312-3J 8312-3J

審査請求 未請求 (全2頁)

❷考案の名称

クリップとグロメットとからなる取付部材

ூ実 顧 昭60-130746

母出 朗 昭60(1985)8月27日

の考案 者

松永 祐介

横浜市神奈川区宝町2番地 日産自動車株式会社内

の出 随 人

日産自動車株式会社

横浜市神奈川区宝町2番地

90代理人 弁

弁理士 西脇 民雄

砂実用新薬登録請求の範囲

クリップと該クリップを挿入する係止孔部を有するグロメットを複数組み合わせて、グロメットを複数組み合わせて、グロメットを具備した第一部材を取り付けるクリップとグロメットとからなる取付部材において、

少なくとも一つのグロメットのクリップを挿入 する保止孔部を、該クリップを具備した第二部材 の長手方向に適宜長さ延長した保止孔部としたこ とを特徴とするクリップとグロメットとからなる 取付部材。

図面の筋単な説明

第1図乃至第5図は、本考案に係るクリップと グロメットとからなる取付部材の好ましい実施例 を示すものである。第1図は取り付けるべき部材 の長手方向の断面図、第2図は第1図におけるII ー II 線に沿う矢視図、第3図は同じくII ー II 線に沿う矢視図、第3図は同じくIV ー IV線に沿う断面 図である。第5図は、取り付けるべき部材の取付 位置が他の部材によって規制されている状態を示す、取り付けるべき部材の長手方向断面図である。第6図及び第7図は従面グリップとグロメットとからなる取付部材を示すもので、第6図はクリップとグロメットとの係合状態を示した断面 図、第7図は第1図に相当する長手方向の断面図である。

1……サイドガードモール、2……車体パネル、4……クリツブ、4 a……係止頭部、5 a, 5 b……グロメツト、3 l a, 5 l b……係止孔部、5 2 a, 5 2 b……係止発起。

